



MONDO PLAST

cabluri si echipamente de telecomunicatii

www.mondoplast.ro www.braungroup.ro www.cables.ro www.nextra.info

Timisoara, Str. Gloriei, 11
tel: 0256-200.321 fax: 278.011

Bragadiru, Sos. Alexandriei, 72-74
tel: 021-420.1310 fax: 420.0057

Mondo Plast SRL

CIF: RO 12765240

capital social: 360.000 RON

J11/53/2009

tel: 0256-278.000 -029 (30 linii)

Timisoara : timisoara@mondoplast.net

Bucuresti : bucuresti@mondoplast.net



CABLURI COAXIALE 50 OHM - DATE & RADIOCOMUNICATII		EURO/m
RG58 NEXTRA	Centr.Cu-St 19x0,18mm, tresa 90%Cu-St, aten.15,1/26,5/49,6dB la 100/300/1000MHz, diam.4,9mm, role 305m	0.29
RG 58	BELDEN Centr.Cu-St 19x0,18mm, tresa 93%Cu-St, aten.15,1/26,5/49,6dB la 100/300/1000MHz, diam.4,95mm, role 305m	0.75
H 159	BELDEN Centr.Cu 1,2mm, folie Al+tresa 70%Cu-St, diam.6,15mm, role 100-500m - OF.SPECIALA in limita stoc	0.60
H 155	BELDEN Centr.Cu 19x0,28mm, folie Al+tresa 80%Cu-St, aten.9,3/16,3/30,9dB la 100/300/1000MHz, diam.5,4mm, role 305m	0.60
RG213 NEXTRA	Centr.Cu 7x0,75mm, tresa 80%Cu, aten. 6,6/11,6/22,6dB la 100/300/1000MHz, diam.10,3mm, role 100-500m	0.95
RG 213	BELDEN Centr.Cu 7x0,75mm, tresa 93%Cu, aten. 6,6/11,6/22,6dB la 100/300/1000MHz, diam.10,3mm, role 100-500m	1.50
RG213-25%	Centr.Cu 2,25mm, tresa 25%Cu, aten. 6,5/11,6/22,1dB la 100/300/1000MHz, - OF.SPECIALA in limita stoc	0.85
H 500	BELDEN Centr.Cu 2,5mm, folie Cu+tresa 50%Cu, aten.4,1/7,5/14,6dB la 100/300/1000MHz, diam.9,8mm, role 100-500m	1.60
H 1000	BELDEN Centr.Cu 2,62mm monofilar, folie+tresa 50%Cu, aten.4/14dB la 100/1000MHz, diam.10,3mm, role 100-500m	1.75
H10000	BRAUN Centr.Cu 2,62mm monofilar, folie+tresa 50%Cu, aten.4/14dB la 100/1000MHz, - OF.SPECIALA in limita stoc	1.30
H 1001	BELDEN Centr.Cu 2,7mm multifilar, folie+tresa 50%Cu, aten.4,7/16,2dB la 100/1000MHz, diam.10,3mm, role 100-500m	1.90

CABLURI COAXIALE 50 OHM - LOW LOSS RF & WIRELESS

Tip RG174 - RF100 - LMR100		EURO/m
7805R	Centr.Cu 0,50mm, tresa 90%Cu-St+folie dubla AL, aten.26,1/66,4/116,3dB la 150/900/2500MHz, diam.4,75mm, role 305m	0.86
Tip RG58 - RF195 - LMR195		EURO/m
7806R	Centr.Cu 0,94mm, tresa 90%Cu-St+folie dubla AL, aten.13,3/33,8/60,1dB la 150/900/2500MHz, diam.4,75mm, role 305m	1.04
Tip RG58 - RF200 - LMR200		EURO/m
7807R	Centr.Cu 1,12mm, tresa 95%Cu-St+folie dubla AL, aten.12,1/30,1/51,6dB la 150/900/2500MHz, diam.4,75mm, role 305m	1.05
Tip RG8X - RF240 - LMR240		EURO/m
7808R	Centr.Cu 1,45mm, tresa 95%Cu-St+folie dubla AL, aten.9,3/22,9/39,5dB la 150/900/2500MHz, diam.6,35mm, role 305m	1.42
Tip RG8 - RF400 - LMR400		EURO/m
7810R	Centr.Cu 2,74mm, tresa 95%Cu-St+folie dubla AL, aten.4,9/12,6/22dB la 150/900/2500MHz, diam.10,2mm, role 305m	2.54

OFERTA SPECIALA CABLURI BELDEN INDUSTRIALE

COD	Nr perechi	Structura cablu	Impe danta	Izolatie	Diam Cablu	Pret EURO/m	Cantit in stoc
Audio Control and Instrumentation cable - twisted pair conductor							
8778	6 per	cond.multifilar AWG22,ecran individual folie/pered	50 ohm	polipropilena	13m	1.19	12958
Twinaxial computer and instrumentatiuon cable							
9463	1 per	cond.multifilar AWG20, tresa Cu-stanat 93%	78 ohm	polipropilena	17m	0.63	16664
Computer cables low capacitance for EIA RS-485 applications - twisted pair conductor							
9841	1 per	cond.multifilar AWG24, cablu ecran folie+tresa 90%	120 ohm	polipropilena	89m	0.67	13151
9842	2 per	cond.multifilar AWG24, cablu ecran folie+tresa 90%	120 ohm	polipropilena	64m	1.09	17303
Computer cables for EIA RS-232 applications - twisted pair conductor							
9501	1 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	96m	0.35	8928
9502	2 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	64m	0.53	11501
9504	4 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	73m	0.88	5363
9505	5 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	34m	1.05	5246
9506	6 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	34m	1.19	5179
9507	7 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	47m	1.33	6727
9508	8 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	23m	1.47	9393
9509	9 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	48m	1.61	4774
9510	10 per	cond.multifilar AWG24, tot cablul ecranat cu folie	75 ohm	Crom PVC	34m	1.75	4216
Computer cables for EIA RS-232 applications - multiconductor							
9533	3 cond	cond multifilar AWG24, tot cablul ecranat cu folie	-	Crom PVC	11m	0.39	2698
9534	4 cond	cond multifilar AWG24, tot cablul ecranat cu folie	-	Crom PVC	67m	0.49	2356
9536	6 cond	cond multifilar AWG24, tot cablul ecranat cu folie	-	Crom PVC	31m	0.66	2418
9540	10 cond	cond multifilar AWG24, tot cablul ecranat cu folie	-	Crom PVC	19m	1.12	775

TOATE PRETURILE NU CONTIN TVA