



MONDO PLAST

cabluri si echipamente de telecomunicatii

www.mondoplast.ro www.braungroup.ro www.cables.ro www.nextra.info

Timisoara, Str. Gloriei, 11
tel: 0256-200.321 fax: 278.011

Bragadiru, Sos. Alexandriei, 72-74
tel: 021-420.1310 fax: 420.0057

Mondo Plast SRL CIF: RO 12756240 capital social: 350.000 RON J11/53/2000

tel: 0256-278.000 -029 (30 linii)

Email : timisoara@mondoplast.net, bucuresti@mondoplast.net

CABLURI FIBRA OPTICA SINGLE MODE



PARAMETRI OPTICI AI FIBRELOR SINGLE-MODE MATCHED-CLADDED

Tip fibra	Diametru miez conductor optic	Diametru acoperire optica cu fibra sticla	Diametru fibra cu invelis acrilic	Lungimea de unda	Atenuare medie	Dispersie ps/(nmxkm)	Index de refractie
SM 9/125	9,3 mm	125 mm	250 mm	1310 nm	0,33 dB/km	< 3,5	1,467
				1550 nm	0,2 dB/km	< 18	1,467

Numar fibre	Diametru cablu	Greutate	Tensiune intindere	Raza min. de curbura	Temperatura de operare	Dimensiuni standard	Pret EURO/m
CABLU TYPE 12 PE - Central tube, metalfree, protectie ultraviolete, protectie rozatoare							
4 x 9/125	5,6 mm	23 kg/km	700 N	120mm	OFERTA SPECIALA		0.30
8 x 9/125	5,6 mm	23 kg/km	700 N	120mm	-30 +70	2000m, 4000m	0.42
12 x 9/125	5,6 mm	23 kg/km	700 N	120mm	-30 +70	2000m, 4000m	0.51
CABLU TYPE 24 PE - Central tube, metalfree, protectie ultraviolete, protectie rozatoare							
4 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	0.66
8 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	0.78
12 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	0.88
24 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	1.20
CABLU TYPE 24 RP - Central tube, metalfree, protectie ultraviolete, protectie imbunatatita rozatoare							
4 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	0.73
8 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	0.84
12 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	0.94
24 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	1.25
CABLU TYPE 48 dcPE - Multi tube, metalfree, protectie ultraviolete, protectie rozatoare							
6 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	0.80
12 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	0.95
24 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	1.22
36 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	1.40
48 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	1.60
CABLU TYPE 48 dcPER - 4000N, Multi tube, metalfree, protectie ultraviolete, protectie rozatoare							
6 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	0.91
12 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	1.02
24 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	1.25
36 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	1.47
48 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	1.69
CABLU TYPE 36 PE AERIAL (Figure 8) - Multi tube, 2 sufe metalice, protectie ultraviolete							
6 x 9/125 Figure 8	11/20mm	195 kg/km	4800 N	165 mm	-30 +70	2000 m	1.20
12 x 9/125 Figure 8	11/20mm	195 kg/km	4800 N	165 mm	-30 +70	2000 m	1.33
24 x 9/125 Figure 8	11/20mm	195 kg/km	4800 N	165 mm	-30 +70	2000 m	1.52
SPIRALE DE INTINDERE / SUSTINERE PT FIBRA OPTICA						RIBE OPTOFIT	EURO
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic diam. 6,12-6,8mm							4.7
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic diam. 7,7-8,3mm							6.0
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 9,7-10,5mm pt deschideri <= 70m							7.3
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 10,51-11,36mm pt deschideri <= 70m							7.3
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 11,37-12,28mm pt deschideri <= 70m							7.3
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 12,29-13,27mm pt deschideri <= 150m							7.3
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 13,28-14,35mm pt deschideri <= 150m							8.6

TERMEN DE GARANTIE PENTRU CABLURILE OPTICE 15 ani.

PRETURILE NU INCLUD TVA